

Backhoe with bucket, w=400 mm

29.52-36-72-000-1

Backhoe is determined to dig the soil slots and holes up to and including the class 3, in the whole rotating range of jib in rotating suspension. Its main advantage is possible digging next to the walls able by moving working device to the side.



Technical specification		réf : 29.52-36-72-000-1
Bucket width		400 mm
Maximum excavating depth		2,5 m
Backhoe weight		755 kg
Backhoe width		1740 mm
Backhoe lenght		1995 mm
Backhoe height		2330 mm



Backhoe with bucket, w=400 mm
Backhoe with bucket, w=400 mm, with distributor HCD4/6

MZ 80001
MZ 80001 H

Backhoe is determined to dig the soil slots and holes up to and including the class 3, in the whole rotating range of jib in rotating suspension. Its main advantage is possible digging next to the walls able by moving working device to the side.



Technical specification	Réf : MZ 80001 (H)
Bucket width	400 mm
Maximum excavating depth	2,5 m
Dumping height	1,8 m
Backhoe weight	750 kg
Backhoe width	1150 mm
Backhoe lenght	960 mm
Backhoe height	1850 mm



Drainage bucket, w=400 mm

MZ 80040

Drainage bucket, w=550 mm

MZ 80055

Slope bucket, w=1000 mm

MZ 80100

Drainage bucket, w=280 mm with self-emptying system

MZ 80028

MZ 80040 , MZ 80055, MZ 80100, MZ 80028 are suitable for L752, L753, L853, L903.

MZ-800 shifted backhoe equipment is a working attachment for skid-steer loaders intended for digging canals, trenches and ditches, for demolition and dozing work.



Model	MZ 80040	MZ 80055	MZ 80100	MZ 80028
Width	400 mm	550 mm	1000 mm	280 mm
Length	850 mm	850 mm	600 mm	800 mm
Height	610 mm	610 mm	500 mm	650 mm
Weight		70 kg	70 kg	60 kg

